

# MDVR-INERT

Inertial sensor



## PRODUCT SPECIFICATIONS

### PRODUCTS FEATURES

- X, Y, Z total 3 dimensions measurement
- Rapid response, instantly acquire accelerated speed
- High sensitivity
- High reliability
- Excellent deviation stability
- Low power consumption
- Rugged design, solid structure, advanced shockproof

### PRODUCT DESCRIPTION

Inertia Sensor is an electronically device which is able to measure vehicle environmental temperature, speeding during driving. It collects mobile device (MDVR) environment temperature through internal temperature sensor and trigger temperature alarm when temperature is higher than the threshold configured. If 3G is connected this alarm can be reported to CMS (Central Monitoring System).

Based on the measured accelerated speed, it is able to simulate the driving condition and incidents such as car crashing, leaning, movement and vibration etc. Likewise, once the value is beyond the valued configured on MDVR GUI, the MDVR system will trigger alarm and this alarm can be reported to CMS as well if 3G is applied. Generally, this is a device helps to judge and record driver's behavior and record the accident when it happens for post-event analysis.



\* For higher accuracy, Please locate inertia sensor horizontally on the vehicle



XTS Corp. Headquarters  
8880 N.W 18th Terrace,  
Doral, FL 33172  
P: 305.863.7779  
F: 305.863.7478  
TF: 1.855.797.8XTS  
[www.xtscorp.com](http://www.xtscorp.com)

# TECHNICAL SPECIFICATIONS

PRODUCT SERIES		INERTIAL SENSOR (G-FORCE SENSOR)
Acceleration	Direction	X, Y, Z 3 axis
	Measuring range	4/12 (G) optional
	Sensitivity	308mV/g OR 83.6mV/g
	Reaction time	0.5 millisecond
Temperature Sensor	Temperature Range	-40/110 ± 0.30+0.006
	Reaction time	< 250 millisecond
Communication	RS-485	
Transmission period	100ms	
Power Supply	5V	
Working Temperature	-30°C □ 70°C	
Wire length	1050mm	
Weight	78g	
Dimension	72mm*66mm*28mm	
Acceleration	Direction	
Measuring range	4/12 (G) optional	
Sensitivity	308mV/g OR 83.6mV/g	
Reaction time	0.5 millisecond	
Temperature Sensor	Temperature Range	
Reaction time	< 250 millisecond	

\* Subject to change without notice



XTS Corp. Headquarters  
 8880 N.W 18th Terrace,  
 Doral, FL 33172  
 P: 305.863.7779  
 F: 305.863.7478  
 TF: 1.855.797.8XTS  
[www.xtscorp.com](http://www.xtscorp.com)