

LED32SM

32" LED CCTV MONITOR



PRODUCT SPECIFICATIONS

PRODUCT FEATURES

- LED CCTV Monitor 32"
- 1366 x 768 high resolution
- Fast response of 6 mS
- MTBF over 50,000 hours
- BNC, HDMI and VGA video inputs
- On Screen Display Menu
- PIP Picture in Picture, PBP Picture by Picture
- Noise reduction, Speakers
- HDMI and VGA cables included
- NTSC & PAL
- 12VDC



PRODUCT CAPABILITIES

The LCD32SM is a monitor for surveillance applications designed to provide outstanding color and clarity aimed to maximize a professional's investment. Powered by the best display innovations and a High Resolution 32", professional grade panel, XTS LED monitors are the perfect choice for modern CCTV industry applications.

Looping Dual Composite BNC, VGA and HDMI video channels and interlacing technology, XTS LED monitors offer a high contrast ratio and deliver Industry Leading Performance. Professional systems will benefit from its picture reproduction of more than 16 million colors and one of the sharpest, brightest video pictures, which display scenes on screen with impressive fidelity to those in the real world.

XTS LED backlit Monitors are engineered specifically to meet the specific demands of the security industry to save energy, generate lower levels of heat and offer extended dynamic contrast. Real low 6ms response, two speakers and advanced noise reduction filter increase the range of application for your XTS LED Monitors.

XTS monitors count up to an exceptional viewing experience and our manufacturing quality is backed up by a loyal three year warranty.

All monitor models 32" and larger do not come with a base stand, as they are too large to be supported. All monitors 32" and larger include a VESA Mounting template (VESA Mount must be ordered separately) to provide convenience in Wall Mounting.



TECHNICAL SPECIFICATIONS

GENERAL

Size	32"
Pixel Format	1366 x 768
Pixel Pitch	0.5107 x 0.5107
Brightness	420 cd/m ²
Contrast Ratio	1000:1
Aspect Ratio	16:10
Viewing Angle	178° H – 178° V
Color Depth	16.7 million colors
Response Time	6ms
Video System	NTSC/PAL
Typical Panel Life	50,000 Hours
Illumination	LED Backlight
Auto Adjustment	VGA Mode
De-interlace	Yes
OSD Control	Color Temp, DNR, Contrast, Brightness, Color, Tint, Sharpness, PictureMode
Functions	PIP, Picture in Picture
Languages	English, Spanish, French, Italian and 6 more
Remote Control	IR Handheld, Included
CCTV in/out	2 BNC Inputs/Outputs
Video Inputs	1 HDMI / 1 VGA
Max Resolution	1366 x 768
Audio Inputs	RCA L + R (STEREO), PC Audio
Speakers	2 x 1.5W
Accessories	HDMI Cable and VGA cable Included
Voltage	100-240 VAC 50/60 HZ cable included
Power Consumption	120W Power Saving Mode ON (100VAC)
Operation Temperature	0° to 40°C (32°F to 104°F)
Storage Temperature	-10° to 60°C (14°F to 140°F)
Operation Humidity	10% to 90% relative, non condensing
Weight	14Kg (31LB)
Cabinet Color	Black
Vesa Mount Template	100mm x 100mm
Certifications	FCC, CE, Power adaptor



XTS Corp. Headquarters
 8880 N.W 18th Terrace,
 Doral, FL 33172
 P: 305.863.7779
 F: 305.863.7478
 TF: 1.855.797.8XTS
www.xtscorp.com