

# HPS124/ HPS129/ HPS1218

POWER SUPPLIES 12V DC



## PRODUCT SPECIFICATIONS

### PRODUCT FEATURES

- Integral Surge Protection
- Individual LED power Indication
- Reverse polarity protected
- Short circuit protection
- Unit maintains camera synchronization
- Power ON/OFF Switch
- Includes power supply, enclosure and transformer
- Easy installation



### PRODUCT CAPABILITIES

The XTS-HPS power supplies convert 110 VAC input power to 12VAC output power and are designed to be used in a variety of CCTV and security applications. They include a pre-drilled mounting flange that allows easy wall mounting and a individual Fuse output protection (2A/250V) with LED power indicator, that offers superior functional life performance and protection due to a unique polymer formulation.

It also offers integral surge protection, vented housing for cooler operation and 3 conductor US type power cord.



## TECHNICAL SPECIFICATIONS

### POWER SUPPLIES

Model	HPS124	HPS129	HPS1218
Output	DC12V	DC12V	DC12V
Input	110VAC	110VAC – 220VAC Selectable	110VAC – 220VAC Selectable
Amps	5 amp (1.25 x Ch)	10 amp (1.11 x Ch)	20 amp (1.11 x Ch)
Fuse	Glass fuse 2A/250V	Glass fuse 2A/250V	Glass fuse 2A/250V
Dimensions	9.75" (L)x 8.125" (W) x 2.75" (D)	9.75" (L)x8.125" (W)x3.75" (D)	9.75" (L) X 8.125" (W) x 3.75" (D)
Shipping Weight	8.3 lb	8.3 lb	8.3 Lb.

Subject to change without prior notice  
BC03282014



XTS Corp. Headquarters  
8880 N.W 18th Terrace,  
Doral, FL 33172  
P: 305.863.7779  
F: 305.863.7478  
TF: 1.855.797.8XTS  
[www.xtscorp.com](http://www.xtscorp.com)

