

HPS124/ HPS129/ HPS1218

POWER SUPPLIES 12V DC



PRODUCT SPECIFICATIONS

PRODUCT FEATURES

- Integral Surge Protection
- Individual LED power Indication
- Reverse polarity protected
- Short circuit protection
- Unit maintains camera synchronization
- Power ON/OFF Switch
- Includes power supply, enclosure and transformer
- Easy installation



PRODUCT CAPABILITIES

The XTS-DPS power supplies convert 110 VAC input power to 24VAC output power and are designed to be used in a variety of CCTV and security applications. They include a pre-drilled mounting flange that allows easy wall mounting and a individual Fuse output protection (2A/250V) with LED power indicator, that offers superior functional life performance and protection due to a unique polymer formulation.

It also offers integral surge protection, vented housing for cooler operation and 3 conductor US type power cord.



TECHNICAL SPECIFICATIONS

POWER SUPPLIES

Model	HPS124	HPS129	HPS1218
Output Voltage	DC12V	DC12V	DC12V
Input Voltage	110VAC	110VAC – 220VAC Selectable	110VAC – 220VAC Selectable
Number of Outputs	4	9	18
Total Output Current	5A (1.25AxCh)	10A (1.1AxCh)	20A (1.1AxCh)
Dimensions	9.75" (L) x 8.125" (W) x 3.75" (D)	9.75" (L) x 8.125" (W) x 3.75" (D)	9.75"(L) X 8.125"(W) x 3.75"(D)
Shipping Weight	11Lbs	11Lbs	11Lbs



XTS Corp. Headquarters
8880 N.W 18th Terrace,
Doral, FL 33172
P: 305.863.7779
F: 305.863.7478
TF: 1.855.797.8XTS
www.xtscorp.com

